

BASIC PAINT SYSTEMS

Plastics

Recommended Primer- Key Primer

Recommended Finish Paints- Eurolux, ECO*, Hollandlac (*preferred finish paint)

Additional Information- If using Hollandlac, 1 coat of FPE Oil Primer/Undercoat must be applied over Key Primer before topcoating.

Ferrous Metal (iron/steel)

Recommended Primer- Ferrous Metal Primer

Recommended Finish Paints- Hollandlac*, ECO (*preferred finish paint)

Additional Information- If unsure of type of metal, a magnet will not stick to non-ferrous metals.

Non-Ferrous Metal (aluminum, copper, etc.)

Recommended Primer- Key Primer

Recommended Finish Paints- Hollandlac*, ECO (*preferred finish paint)

Additional Information- If using Hollandlac, 1 coat of FPE Oil Primer/Undercoat should be applied over Key Primer before topcoating.

Sheetrock

Recommended Primer- Eurolux Primer

Recommended Finish Paint- Eurolux

Plaster

Recommended Primer- Oil Primer/ Undercoat (1st choice), Eurolux Primer (2nd choice)

Recommended Finish Paint- Eurolux, Matte Oil Wallpaint

Additional Information- If using Matte Oil Wallpaint, prime with Oil Primer/Undercoat which is suitable for both Matte Oil or Eurolux.

Exterior Wood Trim & Siding

Recommended Primer- Oil Primer/ Undercoat, ECO Primer

Recommended Finish Paints- Hollandlac, ECO* (*preferred finish paint)

Additional Information- It is strongly suggested that all six sides of new exterior wood be primed prior to installation with double-priming of end grains. Optimal system is Oil Primer/ Undercoat with ECO finish paint.

Azek™

Recommended Primer- Key Primer

Recommended Finish Paint- ECO

Masonry surfaces/ stucco/ HardiPlank™/ cement siding

Recommended Primer- Eurolux Masonry Primer

Recommended Finish Paints- Eurolux, Eurolux Housepaint

Wooden Floors

Recommended Primer- Oil Primer/ Undercoat (2 thin coats of primer, sanding between coats with 150 grit sandpaper)

Recommended Finish Paint- Hollandlac Brilliant (3 coats, allow walking surfaces 28 days to cure to maximum hardness before exposing to heavy traffic)

Existing Wood Siding in sound condition, no prior paint failure and at least 50 years old

Recommended Primer- For enhanced durability and performance, prime with FPE Oil Primer/ Undercoat (1st choice) or ECO Primer after preparation and washing with powdered detergent.

Recommended Finish Paint- ECO*, Eurolux Housepaint (*preferred finish paint)

Existing Wood Siding which has experienced previous paint failure

Recommended Primer- If failure is moisture-related, it is best in most cases to use no primer.

Recommended Finish Paint- Eurolux Housepaint (this finish paint will behave like a stain and allow entrapped moisture to escape)

MDF (Medium Density Fiberboard)

Recommended Primer- Oil Primer/ Undercoat

Recommended Finish Paints- Eurolux, ECO, Hollandlac

If the substrate you are dealing with is not listed above, please call us directly at 1-800-332-1556 or refer to the Specifier's Manual