



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

1 Identification

Product identifier**Trade name:** Eurolux Universal Primer BW**Application of the substance / the mixture** Paint**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Fine Paints of Europe Inc.

274 West Woodstock Road

Woodstock, VT 05091

USA

info@finepaints.com

Phone: 800.332.1556

Emergency telephone number: Phone: 1.800.332.1556 (Monday-Friday 8:00 a.m. - 5:30 p.m. EDT)

2 Hazard(s) identification

Classification of the substance or mixture

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.

Label elements**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

GHS07

Signal word Warning**Hazard-determining components of labeling:**Talc ($Mg_3H_2(SiO_3)_4$)**Hazard statements**

Harmful if inhaled.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a doctor.

If on skin: Wash with plenty of soap and water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 1)

Additional information:



WARNING: This product, excluding latex paints containing up to 6% silica, can expose you to chemicals including Silicon Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Keep out of reach of children.


Information pertaining to particular dangers for man and environment:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Avoid breathing sanding dust/swarf. Can cause cancer if present as respirable dust.

This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 0
Fire = 0
Reactivity = 0

HMIS-ratings (scale 0 - 4)



HEALTH 1 Health = 1
FIRE 0 Fire = 0
REACTIVITY 0 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

| Dangerous components: | | |
|-----------------------|---|----------|
| 13463-67-7 | titanium dioxide | >10–≤25% |
| 14807-96-6 | Talc (Mg ₃ H ₂ (SiO ₃) ₄) | >10–≤25% |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | ≥0–≤2.5% |

4 First-aid measures

Description of first aid measures

General information:

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

Consult doctor if symptoms persist.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 2)

Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If person is conscious, rinse out mouth.

Do not induce vomiting; immediately call for medical help.

Information for doctor:
Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters
Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

| PAC-1: | | |
|------------|---------------------------|-----------------------|
| 13463-67-7 | titanium dioxide | 30 mg/m ³ |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 30 ppm |
| 38640-62-9 | Bis(isopropyl)naphthalene | 5.6 mg/m ³ |
| 25322-69-4 | Polypropylene glycol | 30 mg/m ³ |
| 532-32-1 | sodium benzoate | 61 mg/m ³ |
| 7632-00-0 | sodium nitrite | 6.4 mg/m ³ |
| 7631-99-4 | Sodium nitrate | 4.1 mg/m ³ |
| PAC-2: | | |
| 13463-67-7 | titanium dioxide | 330 mg/m ³ |

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 3)

| | | |
|------------|---------------------------|-----------------------|
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 33 ppm |
| 38640-62-9 | Bis(isopropyl)naphthalene | 61 mg/m ³ |
| 25322-69-4 | Polypropylene glycol | 330 mg/m ³ |
| 532-32-1 | sodium benzoate | 680 mg/m ³ |
| 7632-00-0 | sodium nitrite | 71 mg/m ³ |
| 7631-99-4 | Sodium nitrate | 45 mg/m ³ |

PAC-3:

| | | |
|------------|---------------------------|-------------------------|
| 13463-67-7 | titanium dioxide | 2,000 mg/m ³ |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 200 ppm |
| 38640-62-9 | Bis(isopropyl)naphthalene | 370 mg/m ³ |
| 25322-69-4 | Polypropylene glycol | 2,000 mg/m ³ |
| 532-32-1 | sodium benzoate | 810 mg/m ³ |
| 7632-00-0 | sodium nitrite | 240 mg/m ³ |
| 7631-99-4 | Sodium nitrate | 270 mg/m ³ |

7 Handling and storage

Handling:**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Information about protection against explosions and fires: No special measures required.**Conditions for safe storage, including any incompatibilities****Storage:** Observe instructions for use / storage.**Requirements to be met by storerooms and receptacles:** No special requirements.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see section 7.**Control parameters****Components with limit values that require monitoring at the workplace:****13463-67-7 titanium dioxide**

| | |
|-----|---|
| PEL | Long-term value: 15* mg/m ³ *total dust |
| REL | See Pocket Guide App. A |
| TLV | Long-term value: 0.2* 2.5** mg/m ³ resp. fraction, *nanoscale,**finescale, A3 |

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 4)

| | |
|---|---|
| 14807-96-6 Talc (Mg₃H₂(SiO₃)₄) | |
| PEL | Long-term value: 20 mppcf ppm (containing <1% Quartz) |
| REL | Long-term value: 2* mg/m ³ *respirable dust; and <1% Quartz |
| TLV | Long-term value: 2* mg/m ³ *no asbestos fibers, resp. particulate matter, E, A4 |
| 112-34-5 2-(2-butoxyethoxy)ethanol | |
| TLV | Long-term value: 10* ppm *Inhalable fraction and vapor |

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures: Wash hands before breaks and at the end of work.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Use suitable respiratory protective device when aerosol or mist is formed.

Filter A/P2

Protection of hands:



Protective gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:

Viscous

Color:

Different according to coloring

Odor:

Product specific

Odor threshold:

Not determined.

pH-value at 20 °C (68 °F):

8–8.5

Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

100 °C (212 °F) (7732-18-5 water, distilled, conductivity or of similar purity)

Flash point:

Not applicable.

Flammability (solid, gaseous):

Not applicable.

Decomposition temperature:

Not determined.

Ignition temperature:

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 5)

Explosion limits:
Lower: Not determined.

Upper: Not determined.

Vapor pressure at 20 °C (68 °F): 23 hPa (17.251 mm Hg) (7732-18-5 water, distilled, conductivity or of similar purity)

Density at 20 °C (68 °F): 1.28–1.31 g/cm³ (10.682–10.932 lbs/gal)

Relative density Not determined.

Vapor density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with
Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:
Dynamic at 20 °C (68 °F): 2,512.48–2,853.7 mPas

Kinematic: Not determined.

Solvent content:
VOC content: ≥2.01–<2.28 %
29.2–29.9 g/l / 0.24–0.25 lb/gal

Solids content: 54.2 %

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
ATE (Acute Toxicity Estimate)

| | | |
|------------|----------|-----------|
| Inhalative | LC50/4 h | 12.9 mg/l |
|------------|----------|-----------|

13463-67-7 titanium dioxide

| | | |
|------------|----------|------------------------|
| Oral | LD50 | >20,000 mg/kg (rat) |
| Dermal | LD50 | >10,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat) |

112-34-5 2-(2-butoxyethoxy)ethanol

| | | |
|--------|------|----------------------|
| Oral | LD50 | 5,660 mg/kg (rat) |
| Dermal | LD50 | 4,000 mg/kg (rabbit) |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 6)

Primary irritant effect:**on the skin:** No irritant effect.**on the eye:** No irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:** Harmful**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint.

| | | |
|------------|---|----|
| 13463-67-7 | titanium dioxide | 2B |
| 14807-96-6 | Talc (Mg ₃ H ₂ (SiO ₃) ₄) | 3 |

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity**Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Not hazardous for water.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

13 Disposal considerations

Waste treatment methods**Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

UN-Number**DOT, IMDG, IATA**

Not regulated.

UN proper shipping name**DOT, IMDG, IATA**

Not regulated.

Transport hazard class(es)**DOT, ADN, IMDG, IATA****Class**

Not regulated.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 7)

Packing group

DOT, IMDG, IATA

Not regulated.

Environmental hazards:

Not applicable.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

UN "Model Regulation":

Not regulated.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

112-34-5 | 2-(2-butoxyethoxy)ethanol

7632-00-0 | sodium nitrite

TSCA (Toxic Substances Control Act):

All components are listed on the Inventory and have the value ACTIVE or are exempt.

Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65
Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories
EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

13463-67-7 | titanium dioxide

A4

14807-96-6 | Talc (Mg₃H₂(SiO₃)₄)

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 | titanium dioxide

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 01/13/2023 / -

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2024

Reviewed on 01/13/2023

Trade name: Eurolux Universal Primer BW

(Contd. of page 8)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4