

Page 1/7

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/04/2017 Reviewed on 04/04/2017

### 1 Identification

- · Product identifier
- · Trade name: Hollandlac Satin TR
- · Recommended Use: Architectural Coating
- · Restrictions on Use: Before use of this product, always read the label and SDS carefully.
- · Importer/Supplier:

Fine Paints of Europe Inc. 274 West Woodstock Road Woodstock, VT 05091

USA

info@finepaints.com

· Emergency telephone number:

Phone: 800.332.15556 (Monday-Friday 8:00 a.m. - 5:30 pm EDT, Saturday 9 a.m. - 4 p.m. EDT)

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Phthalic anhydride

(Contd. on page 2)

Printing date 04/04/2017 Reviewed on 04/04/2017

Trade name: Hollandlac Satin TR

(Contd. of page 1)

#### · Hazard statements

Flammable liquid and vapor.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection.

Use only outdoors or in a well-ventilated area.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazardous	ingredients:	
64742-48-9	Naphtha (petroleum), hydrotreated heavy	20-30%
12001-26-2	Mica present in liquid matrix	2.5-<10%
85-44-9	Phthalic anhydride	0.1-<1%

## 4 First-aid measures

- · Description of first aid measures
- · General information:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 04/04/2017 Reviewed on 04/04/2017

Trade name: Hollandlac Satin TR

(Contd. of page 2)

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO)

- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Cool endangered receptacles with water spray.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Product forms slippery surface when combined with water.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Use only in well ventilated areas.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

· Further information about storage conditions:

Protect from frost.

Keep receptacle tightly sealed.

Store in dry conditions.

US

Printing date 04/04/2017 Reviewed on 04/04/2017

Trade name: Hollandlac Satin TR

(Contd. of page 3)

## 8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Protection of hands:

Use of nitrile rubber (NBR) gloves or equivalent is recommended. Protective gloves should be inspected before each use to ensure that they are not torn, punctured, or made ineffective in any way. A visual inspection will help detect cuts or tears. Any gloves with impaired protective ability should be discarded and replaced.

· Selection and penetration time of glove material:

The selection of suitable gloves does not only depend on the material, and their quality varies from manufacturer to manufacturer. As this product is a mixture of several substances, the resistance of the glove material should be checked prior to use. Consult with the manufacturer of the selected gloves on break through time and do not use the selected gloves beyond the break through time.

· Eye protection: Use of protective eyewear is recommended.

9	Physica	l and	C	remi	cal	prop	perti	ies

· Information on basic physical and · General Information	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	According to product specification	
· Odor:	Characteristic paint odor	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	180 °C (356 °F)	

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.

42 °C (108 °F)

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor
	mixtures are possible.

· Explosion limits:

· Flash point:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

· Vapor pressure at 20 °C (68 °F): 1 hPa (1 mm Hg)

• Density at 20 °C (68 °F): 1.13 g/cm³ (9.43 lbs/gal)

Relative density Not determined.Vapor density Not determined.

(Contd. on page 5)

Printing date 04/04/2017 Reviewed on 04/04/2017

Trade name: Hollandlac Satin TR

(Contd. of page 4)

• Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

 Dynamic at 20 °C (68 °F):
 790 mPas

 Kinematic at 40 °C (104 °F):
 500 mm²/s

 Viscosity KU(20 °C/68°F)
 90 KU

 Flow time ISO 6 Cup(23 °C/73.4°F)
 > 60 s

· Other information No further relevant information available.

### 10 Stability and reactivity

- · Reactivity Not reactive
- · Chemical stability Stable at room temperature
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

## 64742-48-9 Naphtha (petroleum), hydrotreated heavy

 Oral
 LD50
 >5000 mg/kg (rat)

 Dermal
 LD50
 >3000 mg/kg (rab)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

No information available.

US

Reviewed on 04/04/2017 Printing date 04/04/2017

Trade name: Hollandlac Satin TR

(Contd. of page 5)

## 13 Disposal considerations

Dispose of in accordance with local, state, and national regulations.

## 14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1263

- · UN proper shipping name
- $\cdot DOT$ · IMDG, IATA

Paint **PAINT** 

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· IMDG, IATA



· Class 3 Flammable liquids

- · Packing group
- · IMDG, IATA III
- · Environmental hazards:
- · Marine pollutant:
- Warning: Flammable liquids · Special precautions for user
- · Danger code (Kemler):

· EMS Number: · Stowage Category

- F-E,S-E
- · Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

Some ingredients are listed, consult supplier.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 7)

Printing date 04/04/2017 Reviewed on 04/04/2017

Trade name: Hollandlac Satin TR

(Contd. of page 6)

### 16 Other information

This information describes exclusively the safety requirements of the mentioned product and is based on our present knowledge. The information is intended to give you advice about safe handling during i.e. storage, processing, transport and disposal. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Exclusive U.S. Importer: Fine Paints of Europe, Inc. Woodstock, VT. Manufactured by Wijzonol Bouwverven International B.V. in Zwolle, Netherlands.

· Date of preparation / last revision

(day/month/year) 04/04/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 1A: Carcinogenicity - Category 1A

- · Sources Safety Data Sheets of the raw materials
- \* \* Data compared to the previous version altered.

US