



Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

1 Identification

Product identifier

Trade name: Colorant ALK 261 Oxide Green**Application of the substance / the mixture** Dyestuff/Colouring agent

Details of the supplier of the safety data sheet

Manufacturer/Supplier:Fine Paints of Europe Inc.
274 West Woodstock Road
Woodstock, VT 05091
USA

info@finepaints.com

Phone: 800.332.1556

Emergency telephone number: Phone: 1.800.332.1556 (Monday-Friday 8:00 a.m. - 5:30 p.m. EDT)

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Liquids 3

H226 Flammable liquid and vapor.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure
1H372 Causes damage to organs through
prolonged or repeated exposure.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

ethylbenzene

xylene

p-(1,1-dimethylpropyl)phenol

Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 1)

Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 0
 Fire = 2
 Reactivity = 0

HMIS-ratings (scale 0 - 4)



HEALTH 0 Health = 0
 FIRE 2 Fire = 2
 REACTIVITY 0 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Dangerous components:		
1308-38-9	dichromium trioxide	>25–≤50%
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	>2.5–≤25%
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	>2.5–<10%
123-86-4	n-butyl acetate	≤2.5%
1330-20-7	xylene	≥0–≤2.5%
80-46-6	p-(1,1-dimethylpropyl)phenol	≥0.1–<1%
100-41-4	ethylbenzene	≥0.1–≤2.5%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 2)

4 First-aid measures

Description of first aid measures

General information:

Take affected persons out into the fresh air.

Keep warm, position comfortably and cover well.

Consult doctor if symptoms persist.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing:

If person is conscious, rinse out mouth.

Do not induce vomiting; immediately call for medical help.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Mount respiratory protective device.

Environmental precautions: Do not allow product to reach sewage system or any water course.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 3)

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
1308-38-9	dichromium trioxide	2.2 mg/m ³
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
78-92-2	butanol	150 ppm
100-41-4	ethylbenzene	33 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
108-88-3	toluene	67 ppm
PAC-2:		
1308-38-9	dichromium trioxide	24 mg/m ³
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
78-92-2	butanol	220 ppm
100-41-4	ethylbenzene	1100* ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
108-88-3	toluene	560 ppm
PAC-3:		
1308-38-9	dichromium trioxide	140 mg/m ³
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
78-92-2	butanol	10000** ppm
100-41-4	ethylbenzene	1800* ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
108-88-3	toluene	3700* ppm

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 4)

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage: Observe instructions for use / storage.

Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1308-38-9 dichromium trioxide	
PEL	Long-term value: 0.5 mg/m ³ as Cr
REL	Long-term value: 0.5 mg/m ³ as Cr; See Pocket Guide App. C
TLV	Long-term value: 0.003 mg/m ³ as Cr(III); A4; inhalable; soluble: DSEN;RSEN
123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm
1330-20-7 xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 5)

Ingredients with biological limit values:	
1330-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-41-4 ethylbenzene	
BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Pasty
Color:	Green
Odor:	Product specific
Odor threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	154–193 °C (309.2–379.4 °F) (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 6)

Flash point:	~38 °C (~100.4 °F)
Flammability (solid, gaseous):	Flammable.
Ignition temperature:	>200 °C (>392 °F) (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	2 hPa (1.5 mm Hg) (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Density at 20 °C (68 °F):	1.35–1.43 g/cm ³ (11.266–11.933 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic at 20 °C (68 °F):	1,141.3–1,592.43 mPas
Kinematic:	Not determined.
Solvent content:	
VOC content:	19.51–<21.61 % 291.7–309 g/l / 2.43–2.58 lb/gal
Solids content:	80.7 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability The product is stable.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: Oxidizing substances

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Dermal	LD50	>159,515–284,029 mg/kg (rabbit)
Inhalative	LC50/4 h	>877–1,562 mg/l

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 7)

1308-38-9 dichromium trioxide		
Oral	LD50	10,000 mg/kg (rat)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Oral	LD50	>15,000 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	13.1 mg/l (rat)
123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

Primary irritant effect:

on the skin: No irritant effect.

on the eye: No irritating effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)		
1308-38-9	dichromium trioxide	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO ₂)	1
108-88-3	toluene	3
NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 8)

12 Ecological information

Toxicity

Aquatic toxicity:	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
EL0	1,000 mg/l /48h (daphnia)
EL50	>1,000 mg/l /72h (Pseudokirchneriella subcapitata)
	1,000 mg/l /48h (daphnia)
LL50	>1,000 mg/l /96h (Oncorhynchus mykiss)
NOELR	100 mg/l /72h (Pseudokirchneriella subcapitata)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
EL50	4.6–10 mg/l /72h (Pseudokirchneriella subcapitata)
	10–22 mg/l /48h (daphnia)
LL50	10–30 mg/l /96h (Oncorhynchus mykiss)
LOEC	0.203 mg/l /21d (daphnia)
NOEC	0.097 mg/l /21d (daphnia)
NOELR	1 mg/l /72h (Algae)

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number

DOT, IMDG, IATA

UN1263

UN proper shipping name

DOT, IATA

Paint

IMDG

PAINT

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 9)

Transport hazard class(es)

DOT



Class 3 Flammable liquids
Label 3

IMDG, IATA



Class 3 Flammable liquids
Label 3
Packing group
DOT, IMDG, IATA III
Environmental hazards: Not applicable.
Special precautions for user Warning: Flammable liquids
Hazard identification number (Kemler code): 30
EMS Number: F-E,S-E
Stowage Category A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT

Quantity limitations On passenger aircraft/rail: 60 L
 On cargo aircraft only: 220 L

IMDG

Limited quantities (LQ) 5L
Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1308-38-9	dichromium trioxide
1330-20-7	xylene
78-92-2	butanol
100-41-4	ethylbenzene
108-88-3	toluene

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 10)

TSCA (Toxic Substances Control Act):		
1308-38-9	dichromium trioxide	ACTIVE
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ACTIVE
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0
123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
80-46-6	p-(1,1-dimethylpropyl)phenol	ACTIVE
100-41-4	ethylbenzene	ACTIVE

Hazardous Air Pollutants		
1308-38-9	dichromium trioxide	
1330-20-7	xylene	
100-41-4	ethylbenzene	
108-88-3	toluene	

Proposition 65

Chemicals known to cause cancer:		
100-41-4	ethylbenzene	
14808-60-7	Quartz (SiO ₂)	

Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		

Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		

Chemicals known to cause developmental toxicity:		
108-88-3	toluene	

Carcinogenic categories

EPA (Environmental Protection Agency)		
1308-38-9	dichromium trioxide	D, CBD
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II

TLV (Threshold Limit Value)		
1308-38-9	dichromium trioxide	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO ₂)	A2
108-88-3	toluene	A4

NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/16/2023

Reviewed on 02/16/2023

Trade name: Colorant ALK 261 Oxide Green

(Contd. of page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 02/16/2023**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1