

Technical Data Sheet

EUROLUX Interior Flat

100% acrylic ultra flat wall and ceiling paint. Eurolux Interior flat is a low-odor, high performance, fast drying waterborne finish suitable for all properly prepared interior surfaces.

- Fast-drying
- Non-yellowing
- Exceptional resistance to water, solvents and detergents.

PRODUCT

INTENDED USE	Walls, ceilings or any other surface on which a scrubbable, durable, flat, easily maintained finish is required.
SITUATION	Interior
PACKAGING	1 l, 2.5 l
COLORS	All colors available via Fine Paints of Europe color mixing system
GLOSS LEVEL	Matt, approx. 10 G.U. at 60 °
BINDER	Acrylate polymer
PIGMENT	High quality pigments
SOLIDS CONTENT	Approx. 42 volume %
DENSITY AT 68 °F	Approx. 1,34 kg/dm ³
VISCOSITY AT 68 °F	Approx. 121 K.U.
DRYING TIME	Drying time (68 °F / 65 % R.H.): dust-free after approx. 1 hr; recoatable after approx. 6 hr. Drying times are average values and provided as an indication only; actual drying time will depend on weather conditions, film thickness and choice of color. Darker colors, applied in lower temperatures will take longer to dry than whites and lighter colors.
SCRUB RESISTANCE	Class 1, as per DIN EN 13 300 after 28 days.

NOTE: The properties and specifications can vary depending on the color. The values stated are typical.

Technical Data Sheet

APPLICATION

APPLICATION BY	3/8" nap roller, Omega Orel brush or synthetic domestic brush.
DILUTION	Ready to use. If necessary, max. 5 % water.
TOOLS/EQUIPMENT CLEANING	Water.
APPLICATION TEMPERATURE / R.H.	Min. 45 °F - max. 77 °F ambient and substrate temp., relative humidity max. 85 %. Substrate temperature min. 38 °F above dew point.
THEORETICAL COVERAGE	covers approx 130 square feet per liter

STORAGE AND USE PERIOD

STORAGE	Cool and above freezing point; do not allow product quality to deteriorate during storage.
USE WITHIN	12 Months (in unopened packaging) After opening the packaging, the effect of 'preservatives' in the paint may be reduced. In exceptional cases, this can give bacteria and molds free rein from outside, which could spoil the product.

The details in this product data sheet are correct at the time of printing. The information provided about this product is regularly updated, and amendments may therefore be made at any time without notice. Fine Paints of Europe expressly disclaims any and all liability related to damages resulting from errors or omissions in the information provided herein, except in the event of malicious intent or gross negligence.