

Technical Data Sheet

EUROLUX Interior Matte

100% acrylic matte wall paint. Eurolux Interior matte is an odorless, high performance, fast drying waterborne finish suitable for all properly prepared interior surfaces.

- Fast-drying
- Non-yellowing
- Exceptional resistance to water, solvents and detergents.

PRODUCT

| | |
|--------------------|---|
| INTENDED USE | Walls, ceilings or any other surface on which a scrubbable, durable, matte, easily maintained finish is required. |
| SITUATION | Interior |
| PACKAGING | 1 l, 2.5 l |
| COLORS | All colors available via Fine Paints of Europe color mixing system |
| GLOSS LEVEL | Matt, approx. 3-5 G.U. at 60 ° |
| BINDER | Acrylic copolymers |
| PIGMENT | High quality pigments |
| SOLIDS CONTENT | Approx. 39 volume % |
| DENSITY AT 68 °F | Approx. 1,29 kg/dm ³ |
| VISCOSITY AT 68 °F | Approx. 118-123 K.U. |
| DRYING TIME | Drying time (68 °F / 65 % R.H.): dust-free after approx. 1 hr; recoatable after approx. 6 hr. Drying times are average values and provided as an indication only; actual drying time will depend on weather conditions, film thickness and choice of color. Darker colors, applied in lower temperatures will take longer to dry than whites and lighter colors. |
| SCRUB RESISTANCE | Class 1, as per DIN EN 13 300 after 28 days. |

NOTE: The properties and specifications can vary depending on the color. The values stated are typical.

Technical Data Sheet

APPLICATION

| | |
|--------------------------------|---|
| APPLICATION BY | 3/8" nap roller, Omega Orel brush or synthetic domestic brush. |
| DILUTION | Ready to use. If necessary, max. 5 % water. |
| TOOLS/EQUIPMENT CLEANING | Water. |
| APPLICATION TEMPERATURE / R.H. | Min. 45 °F - max. 77 °F ambient and substrate temp., relative humidity max. 85 %. Substrate temperature min. 38 °F above dew point. |
| THEORETICAL COVERAGE | covers approx 160 square feet per liter |

STORAGE AND USE PERIOD

| | |
|------------|--|
| STORAGE | Cool and above freezing point; do not allow product quality to deteriorate during storage. |
| USE WITHIN | 12 Months (in unopened packaging) After opening the packaging, the effect of 'preservatives' in the paint may be reduced. In exceptional cases, this can give bacteria and molds free rein from outside, which could spoil the product. |

The details in this product data sheet are correct at the time of printing. The information provided about this product is regularly updated, and amendments may therefore be made at any time without notice. Fine Paints of Europe expressly disclaims any and all liability related to damages resulting from errors or omissions in the information provided herein, except in the event of malicious intent or gross negligence.