

Technical Data Sheet

EUROLUX Housepaint

EUROLUX Housepaint is an advanced, durable, water thinnable coating that offers the ease of application, weather resistance, flexibility, easy clean up and environmental friendliness associated with first quality waterborne coatings.

- Good hiding power
- Good adhesion
- Filling minor surface flaws

PRODUCT

| | |
|--------------------|---|
| INTENDED USE | Exterior wooden surfaces and properly-primed exterior masonry surfaces. |
| SITUATION | Exterior |
| PACKAGING | 2,5 l |
| COLORS | All colors available via Fine Paints of Europe color mixing system |
| GLOSS LEVEL | Satin, approx. 40-50 G.U. at 60 ° |
| BINDER | Acrylic copolymers |
| PIGMENT | High quality pigments and fillers |
| SOLIDS CONTENT | Approx. 44 volume % |
| DENSITY AT 68 °F | Approx. 1,25 kg/dm ³ |
| VISCOSITY AT 68 °F | Approx. 110-115 K.U. |
| DRYING TIME | Drying time (68 °F / 65 % R.H.): dust-free after approx. 1 hrs; recoatable after approx. 12 hr. |

Drying times are average values and provided as an indication only; actual drying time will depend on weather conditions, film thickness and choice of color. Darker colors, applied in lower temperatures will take longer to dry than whites and lighter colors.

NOTE: The properties and specifications can vary depending on the color. The values stated are typical.

Technical Data Sheet

APPLICATION

| | |
|--------------------------------|---|
| APPLICATION BY | This coating should be applied with a 4-inch synthetic house paint brush. Avoid applying thin coats. A Purdy 4" XL-NYLONIA is recommended. This paint may also be applied by spray. Application by roller will produce a good finish but some minor texture may result. |
| DILUTION | Ready to use. If necessary, max. 5% water. |
| TOOLS/EQUIPMENT CLEANING | Water. |
| APPLICATION TEMPERATURE / R.H. | Do not apply when temperature is below 50°F, above 90°F, or when relative humidity is above 80% |
| THEORETICAL COVERAGE | covers approx 320 square feet per 2.5 liter |

STORAGE AND USE PERIOD

| | |
|------------|--|
| STORAGE | Cool and above freezing point; do not allow product quality to deteriorate during storage. |
| USE WITHIN | 12 Months (in unopened packaging) After opening the packaging, the effect of 'preservatives' in the paint may be reduced. In exceptional cases, this can give bacteria and molds free rein from outside, which could spoil the product. |

The details in this product data sheet are correct at the time of printing. The information provided about this product is regularly updated, and amendments may therefore be made at any time without notice. Fine Paints of Europe expressly disclaims any and all liability related to damages resulting from errors or omissions in the information provided herein, except in the event of malicious intent or gross negligence.