

Technical Data Sheet

EUROLUX Key Primer

Key Primer is a state-of-the-art, waterborne primer, suitable for interior or exterior, for metals, fiberglass and plastics (Note: Not for polyesters or hard PVC).

- Good hiding power
- Good adhesion
- Bonding primer

PRODUCT

INTENDED USE	Bonding primer for use on all metals, galvanized finishes and most plastics, for plastic furniture, gutters, range hoods, plastic shutters and vinyl siding
SITUATION	Interior/Exterior
PACKAGING	.75 l
COLORS	Off white
GLOSS LEVEL	Matt, approx. 3-5 G.U. at 60 °
BINDER	Acrylic copolymers
PIGMENT	High quality pigments
SOLIDS CONTENT	Approx. 45 volume %
DENSITY AT 68 °F	Approx. 1,53 kg/dm ³
VISCOSITY AT 68 °F	Approx. 90-100 K.U.
DRYING TIME	Drying time (68 °F / 65 % R.H.): dust-free after approx. 30 min; recoatable after approx. 8 hr.

Drying times are average values and provided as an indication only; actual drying time will depend on weather conditions, film thickness and choice of color. Darker colors, applied in lower temperatures will take longer to dry than whites and lighter colors.

NOTE: The properties and specifications can vary depending on the color. The values stated are typical.

Technical Data Sheet

APPLICATION

APPLICATION BY	Use synthetic brush or foam “throw away” applicator.
DILUTION	Ready to use. If necessary, max. 5 % water.
TOOLS/EQUIPMENT CLEANING	Water.
APPLICATION TEMPERATURE / R.H.	Do not apply when temperature is below 50°F, above 90°F, or when relative humidity is above 80%
THEORETICAL COVERAGE	covers approx 120 square feet per .75 liter

STORAGE AND USE PERIOD

STORAGE	Cool and above freezing point; do not allow product quality to deteriorate during storage.
USE WITHIN	12 Months (in unopened packaging) After opening the packaging, the effect of 'preservatives' in the paint may be reduced. In exceptional cases, this can give bacteria and molds free rein from outside, which could spoil the product.

The details in this product data sheet are correct at the time of printing. The information provided about this product is regularly updated, and amendments may therefore be made at any time without notice. Fine Paints of Europe expressly disclaims any and all liability related to damages resulting from errors or omissions in the information provided herein, except in the event of malicious intent or gross negligence.